



Description:

The CS-6R DVT is single-point stereo, dual voice coil speaker with a 6.5" woofer featuring a polypropylene cone and butyl rubber surrounds.

The dual .75" tweeters allow high frequencies to be directed to the listener in situations where placement is less than optimal.

A round, magnetic micro-flange grille is included in the box, with a square grille (CI6X-SG) available as an optional accessory. All grilles are paintable and resistant to rust and corrosion.

Features:

- One 6.5 inch polypropylene woofer with butyl rubber surrounds
- Two .75" soft dome tweeters
- Limited Lifetime Warranty
- Auto-Reset Overload Protection
- Absolute Phase Crossover Network
- Ultra-Thin Magnetic Micro-Flange Grille
- Optional accessories: rough-in bracket (RB-14), square micro-flange grille (CI6X-SG)

Applications:

Engineered for home theater or distributed audio applications indoors or out (as long as it is not exposed to direct heavy weather). The CS-6R DVT pairs with Phase Velocity's V52, V62 and V5520.

Warranty Information:

The CS-6R DVT comes with a limited ten (10) year warranty. Products not sold through an authorized dealer/distributor will not be supported by the factory warranty. Warranties are non-transferable.

Phase Technology:

8005 W 110th St
Suite 208
Overland Park, KS 66102
Phone: 913.663.5600
Toll Free: 855.663.5600
Fax: 913.663.3200
www.phasetech.com

CS-6R DVT PRODUCT SPECIFICATIONS

NOMINAL IMPEDANCE	8Ω
SENSITIVITY dB @ 2.83V/1M	87 dB
FREQUENCY RESPONSE	50 Hz - 20 kHz
RECOMMENDED POWER	5 - 100 Watts
TWEETER	(2) .75" (19.05 mm) Variable Axis Soft Dome
MIDRANGE	N/A
WOOFER	6.5" (165.1 mm) Polypropylene w/ NBR Surround
ENCLOSURE TYPE	Infinite Baffle
INPUTS	Metal Push Terminals
GRILLE	White Powder-Coated Magnetic Micro-Flange (paintable)
DIMENSIONS	9.1" (231.14 mm) Diameter x 3.4" (86.4mm) Depth
CUTOUT DIMENSIONS	8.062" (204.8 mm)
MOUNTING DEPTH	3" (76.2 mm)
WEIGHT	2.5 lbs
SHIPPING WEIGHT	3.3 lbs
OPTIONAL ACCESSORIES	Pre-Construction Bracket (RB-14)
REGULATORY - CE	Approved
RoHS	Approved