



TCE1.5 PRODUCT SPECIFICATIONS

NOMINAL IMPEDANCE	8Ω
SENSITIVITY dB @ 2.83V/1M	90 dB
FREQUENCY RESPONSE	65 Hz - 20 kHz
RECOMMENDED POWER	15 - 100 Watts
LR TWEETER	.75" (19.1 mm) Silk/Synthetic Soft Dome
CENTER TWEETER	.75" (19.1 mm) Silk/Synthetic Soft Dome
LR WOOFER	(2) 3" (76.2 mm) Ultra-Long Throw Polypropylene w/ NBR Surround
CENTER WOOFER	3" (76.2 mm) Ultra-Long Throw Polypropylene w/ NBR Surround
BASS RADIATORS	(2) 3" (76.2 mm) Ultra-Long Throw Polypropylene w/ NBR Surround
ENCLOSURE MATERIAL	Black Extruded Aluminum
ENCLOSURE TYPE	Sealed/ Passive Radiator
INPUTS	(2) Euroblock Connector
GRILLE	Pressure Fit Powder-Coated Black Aluminum
COLOR OPTIONS	Brushed Black Aluminum
DIMENSIONS	6.75" (171.5 mm) H x 26.5" (419.1 mm) W x 1.5" (38.1 mm) D
WEIGHT	8.35 lbs
INCLUDED ACCESSORIES	Smoked Acrylic Tabletop Stand, Wall Mount
OPTIONAL ACCESSORIES	N/A
REGULATORY - CE	Approved
RoHS	Approved

Description

The Teatro[®] TCE1.5 is designed as the main front sound stage for a home theater system by providing 3 channels from 2 speaker cabinets. The center channel acoustic information is created by independent speaker elements located in the left and right enclosures. This eliminates the need for a center speaker either under or over the display monitor.

Features

- Two .75 inch (19.1 mm) silk/synthetic soft dome tweeters
- Three 3 inch (76.2 mm) ultra-long throw polypropylene woofers with butyl rubber surrounds
- Two 3 inch (76.2 mm) ultra-long throw polypropylene bass radiators with butyl rubber surrounds
- Absolute Phase[®] Crossover networks ensure that the speaker drivers are acoustically and electronically "in phase" and moving in unison
- Achieves three-channel audio out of only two speakers
- A depth of only 1.5" (38.1 mm)
- Included Accessories: smoked acrylic tabletop stand, wall mount

Applications

A pair of TCE1.5 units consumes minimal wall space while bringing superior audio. The TCE1.5 is ideal for spaces where a dedicated center channel speaker is not a viable option.

For optimal sound, use PhaseTech's P3-35 3-Channel Amplifier with a pair of TCE1.5s.

Warranty Information

The TCE1.5 comes with a limited ten (10) year warranty. Products not sold through an authorized dealer/distributor will not be supported by the factory warranty. Warranties are non-transferable.

PhaseTech[®]

13720 W. 109th St.
Lenexa, KS 66215
Phone: 913.663.5600
Fax: 913.663.3200
Toll Free: 855.663.5600
www.mseaudio.com